

EV162218456US

ADJUSTABLE CONCEALED BODY ARMOR

Inventors: Sandra Leigh Hatfield
Ronda Renee Graves
Wayne Kolveck

Docket No. 51549.TBA

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. 119(e) of U.S. Provisional Application Serial Number 60/404,435, filed August 19, 2002.

FIELD OF THE INVENTION

Various embodiments of the present invention relate to body armor. More particularly, to a body armor that the shoulder straps are concealed and include complete adjustability within the outer shell shoulder.

BACKGROUND OF THE INVENTION

Body armor have saved the lives of many law enforcement officers and military personnel in recent years. Body armor have been available in recent years as a protective panel having overlying layers of a fabric. The comfort of a body armor is an extremely important consideration because of the heat buildup that occurs from wearing a heavy and inflexible vest for the long hours an officer is on duty. In addition, concealing the body armor is another important consideration. Preventing "riding up" of the armor is yet another important consideration.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be more fully understood and further advantages will become apparent when reference is made to the following detailed description of the invention and the accompanying drawings. However, these figures are merely illustrative and are not meant to limit the embodiments of the invention.

FIGS. 1A and 1B are pattern drawings for embodiments of the outside front of the body armor of the present invention;

FIGS. 2A and 2B are pattern drawings for embodiments of the outside back of the body armor of the present invention;

FIGS. 3A and 3B are pattern drawings for embodiments of the inside front and back respectively of the body armor of the present invention;

FIGS. 4A and 4B are pattern drawings for alternative embodiments of the outside back of the body armor of the present invention;

FIG. 5 is an illustration of the fragmentary sectional view of one embodiment of the concealed shoulder strap of the present invention;

FIG. 6 is an illustration of the cross-sectional fragmentary view of the shoulder strap attached to body armor of one embodiment of the concealed shoulder strap of the present invention;

FIG. 7 is an illustration of the cross-sectional fragmentary view of the shoulder strap attached to body armor of another embodiment of the concealed shoulder strap of the present invention;

FIG. 8 is a photograph of the front view of one embodiment of the present invention;

FIG. 8A is a photograph of the fragmentary view of Fig. 8 showing the hidden zipper and the opening for stabilizer tab pull through;

FIG. 9 is a photograph of the back view of one embodiment of the present invention;

FIG. 9A is a photograph of the fragmentary view of Fig. 9 showing the hidden zipper;

FIG. 10 is a photograph of the front view of one embodiment of the present invention showing the stabilizer tab when the outer cover is closed and the tab is threaded through;

FIG. 10a is a photograph of the fragmentary view of Fig. 10 showing a cut-away view of the bottom of the panel with the loop that goes around button on the trouser to hold panel in place; and

FIGS. 11A, 11B and 11C are illustrations of another embodiment of the present invention where FIG. 11A shows the outside front of the body armor, FIG. 11B shows the inside front of the body armor and FIG. 11C shows the outside back of the body armor.

FIGS. 12A and 12B are photographs showing the front and back respectively of one embodiment of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

The present invention is described in relation to its use as a body armor having a front protective section for overlying the chest region of the user, and a rear protective section for overlying the back of a user. The front section includes a front protective panel. Similarly, the rear section includes a rear protective panel. A pair of flexible right and left straps 10 are fastened to right and left shoulder regions, respectively, of the rear section. The straps extend over the right and left shoulders of the user for attachment to corresponding right and left portions of the front jacket.

In one embodiment of the present invention, the shoulder straps are concealed and include complete adjustability within the outer shell shoulder. In another embodiment, the adjustability of shoulder straps 10 are hidden within the outer shell shoulder. FIGS. 5, 5A and 6 are illustrations of this embodiment. FIG. 6 shows that the strap 10 is directly attached to ballistic panel 15 by stitching 12 through ballistic panel 15 and shoulder strap 10. As such, the panel is substantially prevented from shifting during wear and extreme conditions, while substantially eliminating the

common problem of rolling and sagging, which is typically found in soft, flexible vests. FIG. 6 also illustrates that shoulder strap 10 is under outershell fabric 20. The strap 10 may be a neoprene loop system or elastic removable straps. FIG. 7 is an alternative embodiment where shoulder strap 10 is concealed by sandwiching the shoulder strap 10 between top outer layer 20 and middle layer of the outer shell 22.

In yet another embodiment, shoulder strap 10 is attached directly to the ballistics through the system disclosed in U.S. Patent No. 4,989,266, wherein the disclosure is incorporated herein. In an alternative embodiment, shoulder strap 10 is attached by a system of a 4 part outer shell strap attachment system.

In a further embodiment of the present invention, a stabilizer tab 30 is directly sewn to the ballistic panel so as to stabilize the ballistic panel against the body. FIGS. 8 and 8A show an embodiment for the opening for stabilizer tab 30 pull through. FIG. 10 shows another view where stabilizer tab 30, when outer cover is closed and tab 30 is threaded through. In a further embodiment, FIGS. 11 A - C show direct attachment of stabilizer tab 30 to ballistics.

As can be seen from FIGS. 8 through 11, the present invention provides better concealability.

FIGS. 12A and 12 B illustrate the adjustability of side straps 40 on both the front and back of the outer shell.

In yet another embodiment, the outershell is provide with a lining that has increased moisture wicking properties. An example of such lining is "Body Sensor" material. The outershell may be composed of a durable 65/35 poly/cotton material.

In yet a further embodiment, a smooth bi-directional stretch fabric is used on the front center to substantially prevent the uniform shirt from snagging on the fabric and to ensure comfort of the wearer.

In another embodiment, as illustrated in FIGS. 1A, 1B, 2A, 2B, 4A, 4B, 8A, 8B, 9A and 9B, geometric patterns are used to strengthen the seams.

In a further embodiment, topstitching is eliminated to provide a smoother finish and prevent chaffing against the wearer's body.

In yet another embodiment, as illustrated in FIGS. 8, 8A and 9A, ballistics are inserted through the front via "hidden" zipper 50. Alternatively, ballistics may be inserted at the bottom to provide a smooth finish and better concealability.

In another embodiment, the positioning of loop fabric and design of straps allows adjustment to be made at an angle in an position.

In a further embodiment, as illustrated in FIG. 9, cummer band 60 can be attached to the inside of the outershall to provide additional security of the back section of the vest.

FIGS. 3A and 3B illustrate an embodiment having no seams or attachment points and thus, further concealing the body armor.

In yet another embodiment, the pockets on the ballistic panels are sufficiently sized for flexible trauma shields and anti-stab panels. For example, the pockets can be 5 inches by 8 inches and 8 inches by 8 inches.